

High Break Strength • Salt Water Proof • Self-Flushing


- ▶ Low profile Retractable Tether is streamlined when not in use
- ▶ Allows full mobility with tool
- ▶ Disconnectable end allows easy tool change out

▶ Two Mounting Options


Option #1:

Dual-Axis Rotation Clamp-On Belt Clip
Mounts on tool belt or webbing harness
(Installation instructions included)

Fits belts up to 2¼"



Option #2: Snap Clip Mount
Attaches to D-ring



▶ Disconnectable End & Lanyard (Included)

WARNING: Elastic Lanyard must be used with retractor system to ensure maximum tool rating

ACO-0926 Q/C-II Elastic Lanyard Accessory for RT4 Retractor (RT4-5601) 16 oz. Tool Limit

ACO-0205 S/R Elastic Lanyard Accessory for RT3 Retractor (RT3-5601) 32 oz. Tool Limit

▶ Specifications



RT4-5601

- 16 oz. Tool Limit
- 36" Extension
- 3 oz. Retraction Force
- Nylon/Spectra Line
- Stainless Steel Spring & Hardware

RT3-5601

- 32 oz. Tool Limit
- 42" Extension
- 12 oz. Retraction Force
- Nylon/Spectra Line
- Stainless Steel Spring
- Locking Mechanism

RT3-5602
Retract Tool Lanyard
Carabiner

1501 Goodyear Avenue
Ventura, CA 93003
(888) 588-9981 / (805) 658-9922
www.gearkeeper.com
info@gearkeeper.com

6-0036-11 Rev A



Patent # 5,697,572
Patent # 6,591,461
Patent # 6,966,519
Patents Pending