

Gear Keeper



VEST INTEGRATION Smart Phone Tether

WARNING

- Modification of tool tether or components will void tool ratings
- Connecting two or more tethers or adding/extending tether length will void tool ratings.
- Inspect tool tether and tool attachment before each use for wear or damage and repair or replace if necessary
- Inspect tool tether after tool drop for signs of wear or strain and replace if necessary
- Inspect tool attachment after tool drop for signs of slippage and reinstall if necessary
- See Tool Attachment Instructions for proper installation.
- Do not exceed tool weight limits
- Not for personal fall protection
- Do not use around machinery

WARNING

- Attaching a tool that is too heavy to a person can result in injury!
- Max tool weight should be approved by a qualified safety professional.
- NOTE: Tool Lanyard rating may be higher than your approved limit.

NOTE: If unsure of how to use this product or have any questions, contact Hammerhead at:
805-658-9922
info@gearkeeper.com

Hammerhead's Guarantee of Quality

If you are not satisfied with any Hammerhead Product, we will replace it or refund your money within thirty days after purchase through the original dealer. Hammerhead Industries warrants its products against manufacturing defects in workmanship or materials. The warranty is void if the product has been abused beyond normal and sensible wear and tear or used for purposes other than intended.



Security in Your Pocket

- ▶ **Low-profile system is much less obtrusive & cumbersome than bulky coils or cables.**
- ▶ **Mounted in a pocket, it keeps your valuable gear easily accessible but safe & out of the way.**
- ▶ **Threaded Stud securely attaches to garment with structure such as coveralls or vest.**
- ▶ **Easy to Use: Low retraction force does not inhibit use**



ANSI/ISEA 121-2018

Note: Low retraction force is not intended to retract phone—retracts line to minimize entanglement and functions as a safety tether.

Connect to Phone

Option 1 Mount directly to phone or smooth case surface with adhesive pad eye mount.

WARNING: If mounting to a phone case, insure the case is substantial enough such that phone will not fall out if dropped.

Option 2 For rough, rubberized cases that adhesive may not stick to, cut a window for pad eye to attach directly to phone back.


Attach Pad Eye to Surface

- 1 Clean surface and pad eye with alcohol swab
- 2 Attach pad eye with adhesive and press firmly
- 3 Adhesive bond strength increases over time. For best results, install 24 hours prior to use (bond strength 50% after 20 minutes, 90% after 24 hours).

Connect to Garment

Threaded Stud penetrates garment material and threads into back of Gear Keeper until hand tight. Attach to structured material or pocket, NOT directly to mesh material.

WARNING: Prior to use, insure threaded stud is tight.



WARNING: Insure garment material is strong enough to hold stud mount attachment during a drop. Do NOT attach directly to mesh material. After installing, test for structural integrity. If unsure, check with Safety professional or contact manufacturer.

Specifications

- 8 oz. / 227 gm Load Limit
- 3 oz. / 85 gm Retraction Force
- 36" / 91 cm Extension
- Spectra/Nylon Line
- Stainless Steel Spring & Hardware



Patent # 5,697,572
Patent # 6,591,461
Patent # 6,966,519
Patents Pending

5720 Nicolle Street
Ventura, CA 93003
(888) 588-9981 / (805) 658-9922
www.gearkeeper.com
info@gearkeeper.com

6-0039-08

RTS-5420 Smart Phone Keeper
Combo Mount



6 53096 55420 1

WARNING: Prior to use, insure pad eye connection is secure

