

Gear Keeper

**9 oz.
MOLLE
Retractor**

2 MOLLE Attachment Options

**Most GPS Units
FRS Radios
Elec. Devices**

Hammerhead's Guarantee of Quality

If you are not satisfied with any Hammerhead Product, we will replace it or refund your money within thirty days after purchase through the original dealer. Hammerhead Industries warrants its products against manufacturing defects in workmanship or materials. The warranty is void if the product has been abused beyond normal and sensible wear and tear or used for purposes other than intended.

Cable/Line Warranty & Rebuild Policy

All Gear Keeper Retractors are manufactured with the highest quality cable/line. Occasionally inspect the cable/line for signs of wear in order to prevent loss of gear. Hammerhead Industries will replace the cable/line for a service charge of \$8.00.

Please contact Hammerhead Industries for a Return Authorization Number and mailing instructions.

If upon receipt of retractor Hammerhead determines that other components vital to the retractor are worn beyond their useful life, the \$8.00 will be returned and no repair will be done.

WARNING:

**Do Not Release Retractor
End When Fully Extended**

Retraction may be rapid and forceful, resulting in injury and/or damage to the product.

**Grab Your Gear,
Use It, Let It Go...
*It Snaps Back Every Time!***

- Keeps Gear Handy**
- Prevents Loss & Damage**



High Break Strength • Salt Water Proof • Self-Flushing

9 OZ. Retractor For Gear Up to 9 oz
e.g. Most GPSs, FRS Radios, Electronic Devices

Also Available in:

6 oz. e.g. Small Flashlights, Laser Pointers, Medic Shears

3 oz. e.g. Compasses, Knives, Medic Shears



Quick Connect (Q/C)

Allows easy disconnection

Mounting Systems/Product Versions



360° Rotating MOLLE Mount

Compact mount minimizes gear movement

Rotation minimizes resistance & maximizes line life

Remove Velcro Strap

Note: If Velcro Strap is not to be used, retainer bar may be cut off without affecting internal retractor operation

Velcro Strap MOLLE Mount

Ideal for attaching Gear Keeper to the MOLLE System anywhere!

Allows Gear Keeper to pivot up and out during use for minimal resistance & maximum line life

Rotating MOLLE Bracket may be removed without affecting internal retractor operation




Velcro Strap Installation

A. Slide Moveable Loop up against Fixed Loop; then feed Velcro Strap through Retainer and back up through Moveable Loop.

B. Pull up on Velcro Strap so that loops cinch down on Retainer.

C. Feed Velcro Strap around belt or MOLLE webbing; then back through Fixed Loop.

D. Affix Velcro Strap back on itself.



Specifications

• Spectra Nylon Line

• Stainless Steel Spring & Hardware

• 32" Extension

• 9 oz. Retraction Force

• 60 lbs. Breaking Strength



Patent # 5,697,572

Patent # 6,591,461

Patent # 6,966,519

Patents Pending

1501 Goodyear Avenue
Ventura, CA 93003

(888) 588-9981 / (805) 658-9922

www.gearkeeper.com

info@gearkeeper.com 6-0026-26

RT4-5174 Mini GK

9 oz. MOLLE Combo



6 53096 45174 6